

GOCUT 208




Submersible Cutter Pump

PRORIL



Pump specifications

OUTPUT	HEAD	FLOW
0.75kW	Rated : 8m	Rated : 3.3L/s
1HP	Max : 10m	Max : 6.7L/s
SHAFT SPEED		2850rpm
OUTLET		50mm
SOLID PASSAGE		26mm



unit : mm

Weight : 22kg

Features

Pump Type

Electric Submersible Pumps
1-Phase, 3-Phase

Motor

Type: Induction Motor
Poles: 2 Pole
Insulation: Class F
Protector: Circle Thermal Protector
Starter: 1-Phase · Capacitor-Run,
3-Phase · D.O.L.

Lubricant

Food Grade (ISO VG32)

Impeller Type

Semi-Open Channel Cutter

Shaft Seal

Double Mechanical Seal
Silicon Carbide VS Ceramic / Carbon

Bearings

C3 Shielded ball bearings

Cable

PVC (CSA Certified) / H07RN-F
6m or longer upon request

Materials

Pump Casing: Gray Iron
Impeller: Gray Iron
Motor Frame: Gray Iron
Motor Shaft: Stainless Steel

Max. Liquid Temperature

40°C

Max. Submersion Depth

20m

pH Range

pH 5 - pH 8

Guide Rail

GRL-02F